

S70C

SOFT SERVE FREEZER

2 Flavor, Floor, Pasteurization + Air Pump Feed Model









Most Powerful & Versatile High capacity 2-flavor floor model with Auto-Pasteurization

and intelligent controls

Auto-Pasteurization

Significantly reduces frequency of cleaning to every 21 days with scheduled daily auto-pasteurization

Digital Control and Display

Microprocessor control provides access to system settings and additional functions. Digital interface displays critial info as system status, temperatures, dispense count, errors, etc.

Operation Logging

Logs every operation and error to provide history and data for easy troubleshooting

Auto Programming

Allows automatic switching of operation modes based on preset scheduels

Ideal for any restaurants, convenience stores, dessert stands and delis to serve ice cream and gelato with desire for significant reduction in labor cost of cleaning.

Hopper Agitators

Maintain product consistency and prevent product separation

Defrost for Cleaning

Increases efficiency during cleaning by heating frozen product in cylinder

Direct Drive Transmission

Eliminates consumable moving parts and increases transmission efficiency

Safety Protections

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating

Refresh and Revive

Restore perfect consistency automatically to reduce product waste and labor cost while ensuring food safety

Self Closing Valve with Speed Control


Automatically prevents product overflow after dispense; Provides flexibility in dispense rate control






S70C

SOFT SERVE FREEZER





SPECIFICATIONS

Flavors	2 + Twist
Freezing Cylinders	2 x 3.2L / 3.4qt
Mix Hoppers	2 x 12L
Output Capacity (80 grams)	800 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb	Kg/lb (Pump)
Net	263 / 580	273 / 607
Shipping	285 / 628	295/656
Volume	1.09 CBM / 38	8.62 CBF

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	553 / 21.8	710 / 28.0
Depth	706 / 27.8	890/35.0
Height	1613 / 63.5	1730 / 68.1

Electrical	MFS	MCA	Power(kW)
380-415/50/3	20	16	5.5
208-230/60/3	30	26	5.8
208-230/60/1	30	25	5.1

FEATURES	
Control Systems	Two, Digital
Refrigerated Hoppers	ightharpoons
Hopper Agitators	\checkmark
Temperature Display	lacksquare
Standby Mode	\checkmark
Auto Closing Dispensing Valves	ightharpoons
Dispensing Speed Control	ightharpoons
Low Mix Indicator Light & Alarm	ightharpoons
Low Temperature Protection	\checkmark
Motor Overload Protection	
High Pressure Protection	\checkmark
Defrost & Refresh	
Soft Start	\checkmark
Direct Drive Pump	ightharpoons
Auto-Pasteurization	
AVAILABLE OPTIONS	
Water Cooled	\checkmark
Top Air Discharge Chute	

 $[\]boldsymbol{\cdot}$ Above specifications are subject to change without notice