

T890

FROZEN BEVERAGE FREEZER

Two flavor, Countertop, Gravity feed









Most Compact & Versatile

Two flavor countertop model for frozen beverage and smoothies

Fast Freeze Down

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

Simple Control, Easy Operation

Simple and intuitive control system makes operation and viscosity adjustment easy, swift and more precise

Low Mix Indicator

Light turns "ON" at low mix to alert operator to add mix

See-through Dispensing Door

Clear dispensing door design makes product more attractive and serves as great marketing tool

Standby & Indicator

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight; Indicator light turns ON blue under Standby mode

Perfect solution for alcoholic and non-alcoholic frozen beverages in bars, restaurants, hospitals, schools and kiosks

Hopper Agitators

Maintain product consistency and prevent product separation

Self-closing Dispensing Valves

Automatically prevents product overflow after dispense

Safety Protections

- · High pressure switch to prevent compressor overheating
- · Thermal overload to protect from motor overheating

Light Box (Optional)

- Illuminates flavor cards to attract more business
- · Changes color to indicate Low Mix and Standby

One-hand Operated Spinner (Optional)


- · Adds ability to blend and offer more variaties of treats
- Allows for multi-tasking one-hand operation that helps increase productivity and reduce serving time






T890

FROZEN BEVERAGE FREEZER





SPECIFICATIONS

Flavors	2
Freezing Cylinders	2 x 3.8L / 4.0qt
Mix Hoppers	2 x 8.0L / 8.5qt
Output Capacity (250ml)	112 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb	
Net	146 / 325	
Shipping	166 / 369	
Volume	0.48 CBM / 17.10 CBF	

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	476 / 18.7	520 / 20.5
Depth	651 / 25.6	853 / 33.6
Height	950 / 37.4	1090 / 42.9

Electrical	MFS	MCA	Power(kW)
220-240/50/1	15	13	2.0
220-240/60/1	15	13	2.1
110-1 1 5/60/1	20	16	1.6

• 13Amp Plug

• Above specifications are subject to change without notice

FEATURES

Control Systems	Two, Mechanical
Refrigerated Hoppers	lacksquare
Hopper Agitators	\checkmark
Standby Mode	ightharpoons
Auto Closing Dispensing Valves	\checkmark
Low Mix Indicator Light	lacksquare
Low Mix Indicator Alarm	\checkmark
Standby Mode	ightharpoons
Standby Indicator Light	\checkmark
High Pressure Protection	lacksquare
Thermal Overload Protection	

AVAILABLE OPTIONS

Top Air Discharge Chute	~
Spinner	\checkmark
Light Box	\checkmark

SPACEMAN UK